

(12) INTERNATIONAL PUBLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

CORRECTED VERSION

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
21 May 2004 (21.05.2004)

PCT

(10) International Publication Number
WO 2004/041652 A1

(51) International Patent Classification⁷: **B65B 57/14,**
35/46

(21) International Application Number:
PCT/IT2003/000723

(22) International Filing Date:
6 November 2003 (06.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
BO2002A 000706
7 November 2002 (07.11.2002) IT

(71) Applicant (for all designated States except US):
AZIONARIA COSTRUZIONI MACCHINE AUTOMATICHE A.C.M.A. S.P.A. [IT/IT]; Via Cristoforo Colombo, 1, I-40131 Bologna (IT).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SALICINI, Sandro**

[IT/IT]; Via de Giovanni, 14, I-40050 Monterenzio (IT).
STIVANI, Eros [IT/IT]; Via Lombardi, 13, I-40100 Bologna (IT). **CAVALLARI, Stefano** [IT/IT]; Via del Meloncello, 5, I-40135 Bologna (IT).


(74) Agents: **JORIO, Paolo** et al.; c/o Studio Torta S.r.l., Via Viotti, 9, I-10121 Torino (IT).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,

[Continued on next page]

(54) Title: MACHINE FOR FORMING AND WRAPPING STACKS OF PRODUCTS



(57) Abstract: In a machine for forming and wrapping stacks (31) of products (2a), a stacking plate (26), having a number of radial seats (30) for relative stacks (31) of products, rotates in steps about a respective axis (27) to feed each seat (30) along an annular path (P) extending through a loading station (25) for loading individual products (2a), a reject station (32), and an unloading station (33) for unloading stacks (31); the reject station (32) being controlled by a sensor (71) activated selectively by counter-pushers (51), each of which is moved along a relative seat (30) by the individual products (2a) fed successively through an inlet (29) of the seat (30) at the loading station (25).

BEST AVAILABLE COPY



SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report*

(48) Date of publication of this corrected version:

16 September 2004

(15) Information about Correction:

see PCT Gazette No. 38/2004 of 16 September 2004, Section II

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.